

# Combo Kit LXT® DLX2145TJ

18V

Includes : DHP458 Impact Driver and DTD152 Impact Driver



## Models in kit



**Combi Drill LXT®  
DHP458**



**Impact Driver LXT®  
DTD152**

## Combi Drill LXT®

### DHP458

18V • 91 Nm • 0 – 2 000 min<sup>-1</sup>

**Rugged combi drill for heavy-duty screwdriving and drilling**

A powerful drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 91 / 58 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light.



**LXT**

#### ■ Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery protection	✓
No load speed	0 - 400 / 2000 min <sup>-1</sup>
Max. fastening torque Hard/Soft	91 / 58 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 6000 / 30 000 min <sup>-1</sup>
Max. Drilling Diameter in Wood	76 mm
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Concrete	16 mm
Max. Drilling Diameter in Steel	13 mm
Sound Power Level (L <sub>WA</sub> )	95 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Impact Drilling	9,5 m/s <sup>2</sup>

#### ■ User benefits

- Battery protection system automatically shuts off power when the battery level is low

Link to product - [www.makita.com](http://www.makita.com)



## Impact Driver LXT®

### DTD152

18V • 1/4" • 165 Nm • 0 – 2 900 min<sup>-1</sup>

#### Compact brushless impact driver for quick driving

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 165 Nm, suitable for quick driving. A handy LED light for added lighting.



**LXT**

#### ■ Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery protection	✓
No load speed	0 - 2900 min <sup>-1</sup>
Max Fastening Torque Impact Drill	165 Nm
Tightening Capacity Standard Bolt	M5 - M16
Impacts per Minute (IPM)	0 - 3500 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	104 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	93 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	10,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Tool weight with battery (EPTA)	1,3 - 1,6 kg
Product Dimensions (L x W x H):	137 x 79 x 238 mm
Driving Shank	1/4 "

#### ■ User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

Link to product - [www.makita.com](http://www.makita.com)



# Related products kit

## Standard AC

821551-8

Makpac case (3)



122576-8

Stopper Pole



123257-7

Side Handle



251314-2 (2x)

Truss Head Screw M4\*12, Td140D



266622-8

Truss Head Screw M4 X 12



346317-0 (2x)

Belt Hook



452947-8

Bitholder



784637-8 (2x)

Screw Bit, Ph2 – S6, 45 Mm, Double



## Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



## Optional AC

821551-8

Makpac case (3)



## Other - DHP458

User manual

Parts drawing

## Other - DTD152

User manual

Parts drawing