

# Rotary Hammer LXT®

## DHR242

18V • SDS-PLUS • 24 mm • 2.0 J

Professional brushless, three-mode rotary hammer

An efficient rotary hammer for SDS-PLUS bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min<sup>-1</sup>. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete.



### Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery protection	✓
Brushless Motor	✓
Impact Energy	2,0 J
Optimum Drilling Diameter Range in Concrete	6 - 12 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Steel	13 mm
Impacts per Minute (IPM)	0 - 4700 min <sup>-1</sup>
No load speed	0 - 950 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	101 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	90 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

### User benefits

- Brushless maintenance-free and long-life motor
- Body model - delivered without battery and charger.

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ **Optional AC**

183477-5

Grease for SDS Drills and Hammers



---

## ■ **Other**

[User manual](#)

[Parts drawing](#)